



**ASTM F891 SCH 40 SERIES
COEXTRUDED CELLULAR CORE PVC PIPE
DRAIN, WASTE AND VENT (DWV)
MANUFACTURER'S CERTIFICATION**

This is to certify the pipe manufactured by Sanderson Pipe Corporation meets or exceeds the applicable engineering standards listed under ASTM F891.

1. **Materials:** Comply with ASTM D4396 cell classification 11432.
2. **Dimensions / Testing:** All pipe meets or exceeds all performance specifications set forth in the current version of the ASTM F891 standard.
3. **Markings on the Pipe:** Identification of nominal pipe size, plastic pipe material code, schedule size, ASTM designation F891, the labeling "COEXTRUDED CELLULAR CORE PVC PIPE", manufacturer's name and code, the National Sanitation Foundation seal for drain, waste, vent (NSF-dwv). Additional labeling on the pipe will include "NOT FOR PRESSURE".

Manufactured in the USA

Revised Date: October 03, 2014

ASTM F891 PLAIN END FOAM CORE DRAIN, WASTE, AND VENT SPECIFICATIONS

Pipe Size	Outside Diameter (OD)	SCH 40 Minimum Wall	Approx. Weight per foot (lbs.)
1 1/2"	1.900	0.145	0.411
2"	2.375	0.154	0.571
3"	3.500	0.216	1.141
4"	4.500	0.237	1.480
6"	6.625	0.280	2.660

Notes:

Pipe made in 10-foot or 20-foot lengths.

Labeled "NOT FOR PRESSURE".